



- ✓ Transports a wide range of roll carts and dollies
- ✓ Very compact and agile design
- ✓ Loading and unloading from both sides
- ✓ Innovative rooftop shape and tilting technology
- ✓ Safe, ergonomic and user-friendly load carrier handling
- ✓ Very good tracking accuracy
- ✓ Up to 1100 lbs per loading bay



THE SOLUTION



Transports up to 8 roll carts or dollies



Improves the handling of existing fleets

LiftLiner® RC

1 LiftLiner® RC
Max train length

1 pair / 4 loading bays

2 LiftLiner® RC
(8 loading bays)

Max payload per loading bay

1100 lbs

Max train speed 2 LiftLiner® RC

5 mph

U-turn 2 LiftLiner® RC

236 in

Roll Cart Compatibility

Depth 23-31* in

Width 72-34 in

Wheel Diameter 4-5 in

*Without collision protection





KEY BENEFITS

- Reduces:
 - Manual handling
 - Forklift traffic
 - Overall operating costs
- Streamlines parcel and retail operations

CREATING FUTURE-FIT
SMART MOVES
LOGISTIC SOLUTIONS

INNOVATIVE TECHNOLOGY



Two roll carts per mother cart



Easy & efficient loading



Safe & ergonomic unloading



Space saving scissor coupling