



- ✓ Extremely space-efficient & agile
- ✓ Loading and unloading from either sides eliminates sequencing
- ✓ Innovative lifting and tilting technology
- ✓ Fully electric solution
- ✓ Safe, ergonomic and user-friendly load carrier handling
- ✓ Flexible unit for different loads and processes
- ✓ Lifts in 3 seconds and carries 2200 lbs per loading bay



THE SOLUTION



Excellent tracking accuracy



Carries multiple cart sizes

LiftLiner®

1 LiftLiner®	1 pair / 2 loading bays
Max Train Length	4 LiftLiner® (8 loading bays)
Max payload per loading bay	2200 lbs
External width	3.3 ft
External length	10.5 ft
Tare weight	770 lbs
Lifting range	2 in
Train length with 3 LiftLiner®	31.5 ft
Max train speed 3 LiftLiner®	5 mph
Max train speed 4 LiftLiner®	4 mph
U-turn 3 LiftLiner®	14.5 ft
Ground clearance	2.4 in
Max slope	10 %
Coupling system	Crossbar coupling



KEY BENEFITS

- Reduces forklift traffic
- 25% more space-efficient compared to other tugger trains
- AGV compatible
- Improves health & safety

INNOVATIVE TECHNOLOGY

Safe & ergonomic load handling



High ground clearance & tracking ability



Eliminates sequencing for maximum flexibility



Space saving crossbar coupling

